

## TECHNICAL DATA SHEET

### Unfinished Herringbone (square edged) 22x70x300mm

Unfinished / Solid Oak / Brushed / Square Edged / Natural Grade



#### INSTALLATION METHODS

|                         |                   |
|-------------------------|-------------------|
| Fully Bonded            | Yes (recommended) |
| Nailed                  | No                |
| Floated on underlay     | No                |
| Over Underfloor Heating | No                |

#### GRADING CRITERIA

Natural grade includes variations in colour tone from plank to plank, with more noticeable markings such as knots, streaks, sapwood and fine cracks. The grading is perfect for owners who want a non-uniform, natural wood floor.

#### PRODUCT DETAILS

|                                 |                                                                    |
|---------------------------------|--------------------------------------------------------------------|
| Responsible Certification:      | Please ask a member of staff for details                           |
| Janka Hardness Rating:          | 1120 lbf(4980N)                                                    |
| Formaldehyde Emission:          | E1(EN717-1)                                                        |
| Pentachlorophenol Emission:     | <5ppm(CEN/TR 14823)                                                |
| Reaction to Fire Certification: | Cfl-s1(EN13501-1)                                                  |
| Thermal Conductivity:           | NPD                                                                |
| Construction:                   | Solid oak                                                          |
| Species:                        | European Oak (Quercus Robur)                                       |
| Pattern:                        | 1-strip                                                            |
| Process:                        | N/A                                                                |
| Finish:                         | Sanded                                                             |
| Profile:                        | T&G left and right handed blocks                                   |
| Edge Profile:                   | Square Edged                                                       |
| Wear Layer:                     | 12mm                                                               |
| Backing:                        | N/A                                                                |
| Thickness:                      | 22mm                                                               |
| Width:                          | 70mm                                                               |
| Length:                         | 300mm                                                              |
| Pack Size:                      | TBC                                                                |
| Grade:                          | Natural                                                            |
| Maintenance:                    | Comprehensive maintenance instructions and materials are available |

#### INSTALLATION AND WARRANTY

All Prestige Wood Floors must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Prestige Wood Floors warranty only applies to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standards worldwide.

*This technical data sheet was written by Prestige Wood Floors. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs use in the sheet are intended only as illustrations. No rights can be derived from them.*