

TECHNICAL DATA SHEET

Unfinished Herringbone (tumbled edged) 22x70x300mm

Unfinished / Solid Oak / Brushed / Tumbled Edges / Natural Grade



INSTALLATION METHODS

Fully Bonded	Yes (recommended)
Nailed	No
Floated on underlay	No
Over Underfloor Heating	No

GRADING CRITERIA

Natural grade includes variations in colour tone from plank to plank, with more noticeable markings such as knots, streaks, sapwood and fine cracks. The grading is perfect for owners who want a non-uniform, natural wood floor.

PRODUCT DETAILS

Responsible Certification:	Please ask a member of staff for details
Janka Hardness Rating:	1120 lbf(4980N)
Formaldehyde Emission:	E1(EN717-1)
Pentachlorophenol Emission:	<5ppm(CEN/TR 14823)
Reaction to Fire Certification:	Cfl-s1(EN13501-1)
Thermal Conductivity:	NPD
Construction:	Solid oak
Specie:	European Oak (Quercus Robur)
Pattern:	1-strip
Process:	N/A
Finish:	Sanded
Profile:	T&G left and right handed blocks
Edge Profile:	Tumbled Edges
Wear Layer:	12mm
Backing:	N/A
Thickness:	22mm
Width:	70mm
Length:	300mm
Pack Size:	TBC
Grade:	Natural
Maintenance:	Comprehensive maintenance instructions and materials are available

INSTALLATION AND WARRANTY

All Prestige Wood Floors must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Prestige Wood Floors warranty only applies to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standards worldwide.

This technical data sheet was written by Prestige Wood Floors. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs use in the sheet are intended only as illustrations. No rights can be derived from them.